

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application.

LISTING OF CLAIMS:

1. (Currently Amended) A method, comprising:

determining a first gain setting for a communication device optimized for error vector magnitude;

storing said first gain setting in memory in the communication device;

transmitting a calibration signal;

changing a second gain setting until transmit power of the communication device is at a predetermined level;

obtaining a value indicative of the transmit power; and

storing the second gain setting and the value indicative of the transmit power in the communication device's memory.
2. (Original) The method of claim 1 wherein transmitting the calibration signal comprises transmitting a tone or other constant envelope signal.
3. (Original) The method of claim 1 wherein obtaining the value indicative of the transmit power comprises measuring transmit power of the communication device while transmitting said calibration signal.

4. (Original) The method of claim 1 further comprising periodically transmitting the calibration signal, measuring transmit power, and adjusting a gain of an amplifier in the communication device based on the measurement of the transmit power.
5. (Original) The method of claim 4 wherein periodically adjusting the gain of the amplifier comprises adjusting the gain until the transmit power reaches at least a threshold value.
6. (Original) The method of claim 4 wherein determining the first gain setting occurs at an ambient temperature that is different from an ambient temperature at which the calibrator signals are periodically transmitted.
7. (Currently Amended) A method, comprising:
- retrieving a calibrated gain value from memory in the communication device which has been optimized for error vector magnitude;
 - changing a gain of an amplifier in the communication device to have the retrieved calibrated gain value;
 - transmitting a calibration signal;
 - measuring transmit power of the communication device while transmitting the calibration signal until the transmit power reaches at least a threshold value;

computing a new gain value of the amplifier based on the measured transmit power after the transmit power reaches at least the threshold value; and
changing the gain of the amplifier to be the new gain value.

8. (Original) The method of claim 7 further comprising transmitting data packets with the amplifier having the new gain value.

9. (Original) The method of claim 7 wherein transmitting the calibration signal comprises transmitting a tone or other constant envelope signal.

10. (Cancelled).

11. (Cancelled)

12. (Currently Amended) The wireless communication device of claim ~~11~~16 wherein the baseband processor causes the radio to change the gain value, emit the calibration signal and determine the new gain value at periodic intervals during a calibration mode of the wireless communication device.

13. (Currently Amended) The wireless communication device of claim ~~11~~16 wherein the baseband processor causes the radio to change the gain value of the variable gain amplifier until the transmit power is within a predetermined range.

14. (Currently Amended) The wireless communication device of claim ~~11~~16 wherein the baseband processor computes a correction factor to be used to determine the new gain value, the correction factor is a function of the power measurement.

15. (Currently Amended) The wireless communication device of claim ~~11~~16 wherein the calibration signal comprises a tone or other constant envelope signal.

16. (Original) A wireless communication device, comprising:
a baseband processor;
an antenna;
a radio coupled to the antenna and the baseband processor, said radio containing a variable gain amplifier and a power detector that measures transmit power of the communication device;
wherein, after the radio is optimized for error vector magnitude, the baseband processor causes the radio to transmit a calibration signal, change a gain value of the variable gain amplifier until transmit power of the communication device is within a predetermined range.

17. (Original) The wireless communication device of claim 16 wherein the gain value at which the transmit power is within the predetermined range and a value

indicative of the transmit power are stored in non-volatile memory in the wireless communication device.

18. (Original) The wireless communication device of claim 16 wherein, at periodic intervals during while transmitting data packets, the baseband processor changes a gain value of the variable gain amplifier to a previously stored calibration gain value, causes a calibration signal to be emitted, and determines a new gain value for the variable gain amplifier based on a power measurement made while emitting the calibration signal.

19. (Currently Amended) The wireless communication device of claim 16 wherein the calibration signal comprises a tone or other constant envelope signal.

20. (Currently Amended) A storage medium in which code is stored, said code being adapted to be executed by a central processing unit ("CPU") and, when accessed by a CPU, causes the CPU to:

determine a first gain setting for a communication device by calibrating the communication device for error vector magnitude;

store said first gain setting in memory in the communication device;

transmit a calibration signal;

change a second gain setting until transmit power of the communication device is at a predetermined level;

obtain a value indicative of the transmit power; and

store the second gain setting and the value indicative of the transmit power
in the communication device's memory.

21. (Original) The storage medium of claim 20 wherein the calibration signal comprises a tone or other constant envelope signal.

22. (Original) The storage medium of claim 20 wherein the code causing the CPU to obtain the value indicative of the transmit power comprises causing the CPU to measure transmit power of the communication device while transmitting said calibration signal.

23. (Original) The storage medium of claim 20 wherein the code also causes the CPU to periodically transmit the calibration signal, measure transmit power, and adjust a gain of an amplifier in the communication device based on the measurement of the transmit power.

24. (Currently Amended) A storage medium in which code is stored, said code being adapted to be executed by a central processing unit ("CPU") and, when accessed by a CPU, causes the CPU to:

retrieve a calibrated gain value from memory in a communication device
optimized for error vector magnitude;

change a gain of an amplifier in the communication device to have the
retrieved calibrated gain value;

transmit a calibration signal;
measure transmit power of the communication device while transmitting the
calibration signal until the transmit power reaches at least a
threshold value;
compute a new gain value of the amplifier based on the measured transmit
power after the transmit power reaches at least the threshold value;
and
change the gain of the amplifier to be the new gain value.

25. (Original) The storage medium of claim 24 wherein the code also causes
the CPU to transmit data packets with the amplifier having the new gain value.

26. (Cancelled).